APPROVAL SHEET

PRODUCT	**Common Mode Choke (MCM3216B)**
SERIES	MCM3216B
PART NO.	MCM3216BXXXHBE
DESCRIPTION	
ISSUE DATE	2023/11/22
REVISION DATE	2023/11/22
REFERENCE NO.	0003613XXXXX

RoHS COMPLIANCE ITEM

Halogen Free

著作權所有 禁止翻印 華新科技股份有限公司
PSA PASSIVE SYSTEM ALLIANCE
Walsin Technology Corporation
COPYRIGHT © WALSIN TECHNOLOGY CORPORATION. ALL RIGHTS RESERVED.

CUSTOMER APPROVAL

CUSTOMER _____ **CUSTOMER PN** _____

■ **Vendor:** Walsin Technology Corporation
566-1, Kao Shi Road, Yangmei, Taiwan
Tel. 886-3-475-3711 www.passivecomponent.com

■ **Manufacturer:** INPAQ Technology Co., Ltd.
No.11, Ke-Yi St., Chunan, Miaoli 35059, Taiwan
Tel. 886-37-585-555 www.inpaq.com.tw

Note:
- The product is subjected to changes in accordance with individual product change notification (PCN) agreement (if any) or Walsin Technology Corporation's policy.
- Hyperlinks may be included in this document and may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Walsin Technology Corporation disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Copyright © by Walsin Technology Corporation. | All rights reserved.

MCM3216B SERIES (Chip Common Mode Filter) Engineering Specification

RoHS Pb

This product belongs to the industrial grade standard, not the vehicle gauge product! Can not use auto parts, if the customer is not expressly informed and privately used to auto parts, produce any consequences, the original is not responsible for after-sales service, thank you!

Features and Application

. Powerful components with composite co-fired material to solve EMI problem for high speed differential signal transmission line as USB, and LVDS, without distortion to high speed signal transmission.

1. PRODUCT DETAIL

Part No.	Imp. Com. (Ω)±25% @100MHz	DCR Max. (Ω)	Rated Current Max.(mA)	Rated Voltage (V)	Withstand Voltage (V)	Insulation Resistance Min.(MΩ)
MCM3216B900HBE	90	0.50	500	10	25	200
MCM3216B121HBE	120	0.50	500	10	25	200
Test Instruments	•Agilent E4991A RF IMPEDANCE / MATERIAL ANALYZER •HP4338 MILLIOHMMETER • Agilent E5071C ENA SERIES NETWORK ANALYZER •Keithley 2410 1100V SOURCE METER					

2. PART NUMBER CODE

MCM	3216	B	90	0	H	B	E
1	2	3	4	5	6	7	8

1 Series Name
2 Size Code: the first two digitals : length(mm), the last two digitals : width(mm)
3 Material Code
4 Impedance(Ω) ± 25%
5 Fixed Decimal Point
(ex : 900=90Ω ; 121=120Ω)
6 Rated Current Code

A=50mA	B=80mA	C=100mA	D=150mA	E=200mA	F=300mA
G=400mA	H=500mA	I =600mA	J =700mA	K=800mA	


7 Soldering : Green Parts: A– Soldering Lead-Free B– Lead-Free for whole chip
8 Packaging: E - Embossed plastic tape, 7" reel.

Copyright © by Walsin Technology Corporation. | All rights reserved.


3. TYPICAL CHARACTERISTIC

MCM3216B900

IMPEDANCE vs. FREUQENCY CHARACTERISTICS




INSERTION LOSS vs. FREUQENCY CHARACTERISTICS




MCM3216B121

IMPEDANCE vs. FREUQENCY CHARACTERISTICS




INSERTION LOSS vs. FREUQENCY CHARACTERISTICS



著作權所有 侵害必究
華新科技股份有限公司
PSA PASSIVE SYSTEM ALLIANCE
Walsin Technology Corporation
COPYRIGHT © WALSIN TECHNOLOGY CORPORATION. ALL RIGHTS RESERVED.

Copyright © by Walsin Technology Corporation. | All rights reserved.


4. SHAPES AND DIMENSIONS




TYPE	3216
L	3.20±0.20
W	1.60±0.20
T	1.00±0.10
P	2.10±0.20
C1	0.70±0.20
C2	0.30±0.20
Unit: mm	

5. MEASURING CIRCUITS

(A):Common mode




(B):Differential mode




著作權所有 侵害必究
禾新科技股份有限公司

Copyright © by Walsin Technology Corporation. | All rights reserved.


6. CIRCUIT CONFIGURATION & LAYOUT PAD





著作權所有 侵害必究
華新科技股份有限公司
PSA
PASSIVE SYSTEM ALLIANCE
Walsin Technology Corporation
COPYRIGHT © WALSIN TECHNOLOGY CORP. ALL RIGHTS RESERVED.

7. RECOMMENDED SOLDERING CONDITIONS



For lead free solder

Copyright © by Walsin Technology Corporation. | All rights reserved.

8. RELIABILITY AND TEST CONDITION


Test item	Test condition	Criteria
Temperature Cycle	A. Temperature : -40 ~ +85℃ B. Cycle : 100 cycles C. Dwell time : 30minutes Measurement : at ambient temperature 24 hrs after test completion	A. No mechanical damage B. Impedance value should be within ± 20 % of the initial value
Operational Life	A. Temperature : 85℃ ± 5℃ B. Test time : 1000 hrs C. Apply current : full rated current Measurement : at ambient temperature 24 hrs after test completion	A. No mechanical damage B. Impedance value should be within ± 20 % of the initial value
Biased Humidity	A. Temperature : 40 ± 2℃ B. Humidity : 90~95 % RH C. Test time : 1000 hrs D. Apply current : full rated current Measurement : at ambient temperature 24 hrs after test completion	A. No mechanical damage B. Impedance value should be within ± 20 % of the initial value
Resistance to Solder Heat	A. Solder temperature : 260 ± 5℃ B. Flux : Rosin C. DIP time : 10 ± 1 sec	A. More than 95 % of terminal electrode should be covered with new solder B. No mechanical damage C .Impedance value should be within ± 20 % of the initial value

Copyright © by Walsin Technology Corporation. | All rights reserved.

Steam Aging Test	A. Temperature : 93 ± 2℃ B. Test time : 4 hrs(MCA) Others : 8 hrs C. Solder temperature : 235 ± 5℃ D. Flux : Rosin E. DIP time : 5 ± 1 sec	More than 95 % of terminal electrode should be covered with new solder

9. TAPE AND REEL SPECIFICATIONS

Type：Plastic Carrier




Unit：mm

Symbol	Size	Symbol	Size
W	8.00±0.10	Po	4.00±0.10
P1	4.00±0.10	P2	2.00±0.10
E	1.75±0.10	Bo	3.40±0.10
F	3.50±0.10	Ao	1.80±0.10
Do	1.55±0.05	Ko	1.25±0.10
D1	1.00±0.05	t	0.22±0.05

Copyright © by Walsin Technology Corporation. | All rights reserved.

10. REEL DIMENSIONS

Unit: mm



11. STANDARD QUANTITY FOR PACKAGING

Packaging style：Taping
Reel packaging quantity：3000 pcs/reel
Inner box：5 reel/inner box

12. GENERAL TECHNICAL DATA

Operating temperature range : - 40℃ ~ +85℃
Storage Condition : Less than 40℃ and 70% RH
Storage Time: 6 months Max.
Soldering method: Reflow

Copyright © by Walsin Technology Corporation. | All rights reserved.