APPROVAL SHEET

PRODUCT	**Power Inductor (WIP252010S L)**
SERIES	WIP252010S L
PART NO.	
DESCRIPTION	
ISSUE DATE	2023/11/10
REVISION DATE	2023/11/10
REFERENCE NO.	ENS000081910

RoHS COMPLIANCE ITEM

Halogen Free

著作權所有 侵害必究 華新科技股份有限公司 PSA PASSIVE SYSTEM ALLIANCE Walsin Technology Corporation COPYRIGHT © WALSIN TECHNOLOGY CORPORATION. ALL RIGHTS RESERVED

CUSTOMER APPROVAL

CUSTOMER _____ **CUSTOMER PN** _____

■ **Vendor:** Walsin Technology Corporation
566-1, Kao Shi Road, Yangmei, Taiwan
Tel. 886-3-475-3711 www.passivecomponent.com

■ **Manufacturer:** INPAQ Technology Co., Ltd.
No.11, Ke-Yi St., Chunan, Miaoli 35059, Taiwan
Tel. 886-37-585-555 www.inpaq.com.tw

Note:
- The product is subjected to changes in accordance with individual product change notification (PCN) agreement (if any) or Walsin Technology Corporation's policy.
- Hyperlinks may be included in this document and may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Walsin Technology Corporation disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Copyright © by Walsin Technology Corporation. | All rights reserved.

1. Scope

Feature

- High saturation current realized by material properties and structure design
- Low DC resistance to achieve high conversion efficiency and lower temperature rising
- Low Profile: 2.5 mm × 2.0 mm × 1.0 mm.
- Magnetically shielded structure to accomplish high resolution in EMC protection.
- Halogen free, Lead Free, RoHS Compliance.
- Surface marking：None.
- The moisture sensitivity level (MSL) of products is level 1.

Applications

- Smart phone, PAD
- DC/DC converter
- Thin-type power supply module

2. Explanation of Part Number



1 : Series Name: Wire-wound type power inductor
2 : Size Code: The first two digitals: length(mm), The last two digitals: width(mm)
3 : Thickness in mm
4：Material code: Iron powder
5：Initial inductance value: 2R2 = 2.2 μH 6：
Model code, Tolerance of Inductance ±20%.7：
Electrode type.

Copyright © by Walsin Technology Corporation. | All rights reserved.

3. Construction & Dimensions

3.1. End termination: Cu/Ni/Sn

3.2. Construction & Dimensions:



L [mm]	W [mm]	W1 [mm]	T [mm]	E [mm]
2.5±0.2	2.0±0.2	1.8±0.2	1.0 max.	0.6±0.3





3.3. Recommend Land Pattern Dimensions:



A [mm]	B [mm]	C [mm]
2.0	1.2	2.8

4. General specifications

4.1. Temperature Specifications

Operating Temperature range : - 40℃ to +125℃(including self-temperature rising)

Storage Temperature range : - 50°C to +125°C

Copyright © by Walsin Technology Corporation. | All rights reserved.

5. Performance Characteristics

5.1. Specifications

INPAQ Part Number	Li [μH] Initial inductance	RDC [mΩ] DC Resistance		Isat [A] Saturation Current		Irms [A] Heat Rating Current		SRF [MHz]	Quality Factor
		Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Typ.
WIP252010S-R22ML	0.22	10	13.5	10.5	9.0	6.9	6.3	>120	30
WIP252010S-R24ML	0.24	11.5	14.5	8.8	8.0	6.6	6.0	>120	30
WIP252010S-R33ML	0.33	17	22	7.8	7.0	5.6	4.8	>120	30
WIP252010S-R47ML	0.47	23	29	6.6	6.0	5.2	4.4	>120	30
WIP252010S-R68ML	0.68	30	36	5.5	5.0	4.3	3.7	90	30
WIP252010S-1R0ML	1.0	41	52	4.4	4.0	3.4	3.1	70	30
WIP252010S-1R5ML	1.5	62	72	3.8	3.4	2.9	2.5	60	30
WIP252010S-2R2ML	2.2	88	110	3.3	3.0	2.4	2.1	50	30
WIP252010S-3R3ML	3.3	140	160	2.5	2.2	1.9	1.6	40	30
WIP252010S-4R7ML	4.7	200	240	2.2	1.9	1.6	1.4	30	30

Notes

1. Customized design is available, please contact us.
2. All test referenced to 25℃ ambient.
3. Inductance tolerance +/- 20%.
4. Inductance is measured with Agilent® LCR meter 4285A (or equivalent) at 1MHz/1V.
5. DC resistance is measured with HIOKI® micro-ohm meter RM3542 or equivalent.
6. Isat：DC current (A) that will cause Li to drop approximately 30%.
7. Irms：DC current (A) that will cause an approximate ΔT of 40℃.
8. The rated current value is following either Isat (max.) or Irms (max), which value is lower one.
9. The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions. PCB land pattern, trace size - thick, circuit design and proximity to other components are all the factors will affect the temperature performance of the device. Therefore, it should be approved in application conditions and end product.
10. Rated voltage:20V DC (max.)

Copyright © by Walsin Technology Corporation. | All rights reserved.

5.2. Current Characteristic





















Copyright © by Walsin Technology Corporation. | All rights reserved.

5.3. Frequency Characteristic

5.3.1 Inductance & Q factor – Frequency Curve





















Copyright © by Walsin Technology Corporation. | All rights reserved.

6. Reliability and Test Condition

Test item	Test condition	Criteria
Resistance to Solder Heat	1. Solder temperature:260 ± 5℃ 2. Flux: Rosin 3. DIP time : 10 ± 1 sec	1. More than 95 % of terminal electrode should be covered with new solder 2. No mechanical damage 3. Inductance value should be within ± 20 % of the initial value
Adhesive Test	1. Reflow temperature: 245℃ It shall be Soldered on the substrate applying direction parallel to the substrate 2. Apply force(F): 5 N 3. Test time : 10 sec	1. No mechanical damage 2. Soldering the products on PCB after the pulling test force > 5 N
Thermal shock	1. Temperature:-50 ~ 125℃ For 30 minutes each 2. Cycle: 500 cycles 3. Measurement: At ambient temperature 24 hours after test completion	1. No mechanical damage 2. Inductance should be within ±20% of the initial value
Dry Heat Test	1. Temperature: 85 ± 2℃ 2. Testing time: 500 hrs. 3. Applied current: Full rated current 4. Measurement: At ambient temperature 24 hours after test completion	1. No mechanical damage 2. Inductance should be within ± 20% of the initial value
Humidity Test	1. Temperature: 60 ± 2℃ 2. Humidity: 90-95 % RH 3. Applied current: Full rated current 4. Testing time: 500 hrs 5. Measurement: At ambient temperature 24 hours after test completion	1. No mechanical damage 2. Inductance should be within ±20% of the initial value

Copyright © by Walsin Technology Corporation. | All rights reserved.

7. Taping Package and Label Marking

7.1. Carrier tape dimensions (Plastic Tape)



	A0	B0	K0	t
mm	2.25±0.05	2.80±0.1	1.35±0.1	0.22±0.05

7.2. Taping reel dimensions



PART SIZE (EIA SIZE)	**2520 (1008)**
Qty.(pcs)	3,000
BOX	5 reels / inner box

Copyright © by Walsin Technology Corporation. | All rights reserved.

7.3. Taping specifications

There shall be the portion having no product in both the head and the end of taping, and there shall be the cover tape in the head of taping.

7.4. Label Marking

The label specified as follows shall be put on the side of reel.

(1) Part No.

(2) Quantity

(3) Lot No.

* Part No. And Quantity shall be marked on outer packaging.

7.5. Quantity of products in the taping package

(1) Standard quantity：3000pcs/Reel

(2) Shipping quantity is a multiple of standard quantity.

8. Precautions for Handling

8.1. Precaution for handling of substrate

Do not exceed to bend the board after soldering this product extremely.
(reference examples)

- Mounting place must be as far as possible from the position, which is close to the break line of board, or on the line of large holes of board.
- Do not bend extremely the board, in mounting another components.
  If necessary, use back-up pin (support pin) to prevent from bending extremely.
- Do not break the board by hand. We recommend to use the machine or the jig to break it.

8.2. Precaution for soldering

Note that this product will be easily damaged by rapid heating, rapid cooling or local heating.

Do not give heat shock over 100°C in the process of soldering. We recommend to take preheating and gradual cooling.

Copyright © by Walsin Technology Corporation. | All rights reserved.

8.3. Recommendable reflow soldering



Reference IPC-020c-5-1

Profile Feature	Pb free Assembly
Average Ramp Rate (Ts max to Tp)	3 ℃/second max
Preheat - Temperature Min (Ts_{min}) - Temperature Min (Ts_{max}) - Time(ts_{min} to ts_{min})	 150℃ 200℃ 60-180 seconds
Time maintained above: - Temperature (TL) - Time (tL)	 217℃ 60-150 seconds
Peak Temperature (T_p)	260℃ +0/-5 ℃
Time within 5 ℃ of actual Peak Temperature (T_p)	20-40 seconds
Ramp-Down Rate	6 ℃/second max.
Time 25℃ to Peak Temperature	8 minutes max

Copyright © by Walsin Technology Corporation. | All rights reserved.

8.4. Soldering gun procedure

Note the follows, in case of using solder gun for replacement.

(1) The tip temperature must be less than 280°C for the period within 3 seconds by using soldering gun under 30 W.

(2) The soldering gun tip shall not touch this product directly.

8.5. Soldering volume

Note that excess of soldering volume will easily get crack the body of this product.

8.6. Taping Package Storage Condition

Storage Temperature : 5 to 40°C

Relative Humidity: < 65%RH

Storage Time : 12 months max

著作權所有 侵害必究
華新科技股份有限公司
PSA
PASSIVE SYSTEM ALLIANCE
Walsin Technology Corporation
COPYRIGHT © WALSIN TECHNOLOGY CORPORATION. ALL RIGHTS RESERVED.

Copyright © by Walsin Technology Corporation. | All rights reserved.